5.5.5 **P02_FRW125_IP** - incombustible pipes insulated on flexible/rigid wall ≥ 125 mm - PIPEWRAP

Description

- Flexible wall (plasterboard) - thickness ≥ 125 mm.
- Rigid wall (concrete, aerated concrete or masonry) - thickness ≥ 125 mm.
- Application around the pipe of the PIPEWRAP inside the support on both sides.
- PIPEWRAP: thickness 2 mm and width 60/100 mm.



Classification and field of application

Type of pipe	Diameter [mm]	Combustible insulation [mm]	PIPEWRAP thickness [mm]	Classification
Incombustible	10 - 57	9 - 22	60x4 (2 turns)	EI 120 (C/U)
		23-34	60x6 (3 turns)	EI 120 (C/U)
		35-50	60x8 (4 turns)	EI 120 (C/U)
	58 - 63.5	9 - 22	60x4 (2 turns)	EI 90 (C/U)
		23 - 34	60x6 (3 turns)	EI 90 (C/U)
		35 - 50	60x8 (4 turns)	EI 120 (C/U)
	63.5 - 76	9 - 34	60x6 (3 turns)	EI 90 (C/U)
		40 - 50	60x8 (4 turns)	EI 120 (C/U)
	76.1 - 88.9	9 - 22	60x4 (2 turns)	EI 90 (C/U)
		23 - 34	60x6 (3 turns)	EI 90 (C/U)
		50	60x8 (4 turns)	EI 120 (C/U)