5.5.3 **P05_RF150_CP** - combustible pipes on floor ≥ 150 mm - PIPEWRAP

Description

- Rigid floor (concrete, aerated concrete or masonry) - thickness ≥ 150 mm.
- Application around the pipe of the PIPEWRAP inside the support.
- PIPEWRAP: thickness 2 mm and width 60/100 mm.



Classification and field of application

Type of pipe	Diameter [mm]	PIPEWRAP thickness [mm]	Classification
PVC	32 - 110	60x4 (2 turns)	EI 240 (U/C)
	110 - 125	100x8 (4 turns)	EI 240 (U/C)
	125 - 160	100x10 (5 turns)	EI 240 (U/C)
	170 - 185	100x14 (7 turns)	EI 240 (U/C)
	190 - 200	100x16 (8 turns)	EI 240 (U/C)
PE	32 - 110	60x4 (2 turns)	EI 240 (U/C)
	110 - 125	100x8 (4 turns)	EI 240 (U/C)
	140 - 160	100x10 (5 turns)	EI 240 (U/C)
	170 - 200	100x16 (8 turns)	EI 90 (U/C)
PP	32 - 110	60x4 (2 turns)	EI 240 (U/C)
	110 - 125	100x8 (4 turns)	EI 90 (U/C)
	140 - 160	100x10 (5 turns)	EI 90 (U/C)
	160 - 200	100x16 (8 turns)	EI 45 (U/C)