MARVON

5.5.6 **P09_RW150_IP** - incombustible pipes insulated on rigid wall ≥ 150 mm - PIPEWRAP

Description

- Rigid wall (concrete, aerated concrete or masonry) - thickness ≥ 150 mm.
- Application around the pipe of the PIPEWRAP inside the support.
- PIPEWRAP: thickness 2 mm and width 60 mm.



Classification and field of application

Type of pipe	Diameter [mm]	Combustible insulation [mm]	PIPEWRAP thickness [mm]	Classification
Incombustible	10 - 88.9	9 - 23	60x4 (2 turns)	EI 180 (C/U)
		24-36	60x6 (3 turns)	EI 180 (C/U)
		37-50	60x8 (4 turns)	EI 180 (C/U)
	90 - 114	9 - 23	60x4 (2 turns)	EI 60 (C/U)
		24 - 34	60x6 (3 turns)	EI 180 (C/U)
		35 - 50	60x8 (4 turns)	EI 180 (C/U)
	115 - 139.7	9	60x2 (1 turn)	EI 60 (C/U)
		10 - 23	60x4 (2 turns)	EI 60 (C/U)
		24 - 34	60x6 (3 turns)	EI 90 (C/U)
		35 - 50	60x8 (4 turns)	EI 180 (C/U)
	140 - 159	9	60x2 (1 turn)	EI 60 (C/U)
		10-23	60x4 (2 turns)	EI 60 (C/U)
		24 - 34	60x6 (3 turns)	EI 90 (C/U)
		50	60x8 (4 turns)	EI 180 (C/U)
	160 - 200	50	60x8 (4 turns)	EI 90 (C/U)